
## 2-WIRE INTERCOM SYSTEM

# **EXES-6000**

HF-640S DOOR STATION
YC-150 FLUSH-MOUNTED BACK BOX
YC-150E FLUSH-MOUNTED BACK BOX
YS-13 SURFACE-MOUNTED BACK BOX



DOOR STATION (HF-640S)

#### **Features**

- 1. Compact, weather-resistant type intercom station featuring hands-free operation.
- 2. Rugged flush- or surface-mounted type with stainless steel front panel.
- 3. Volume controls to adjust microphone sensitivity
- and speaker output level.
- 4. Call switch to either activate a call bell, chime, etc. or to initiate conversation.
- 5. In-use lamp for eavesdropping protection.
- 6. Non-polar 2-wire system.



#### **General Description**

The HF-640S intercom station for outdoor use is designed to operate in conjunction with the TOA fully electronic exchange, which features a built-in microcomputer with a memory for stored program control. The station can communicate with a designated master station in the system. In addition to intercommunication, there are several other functions designed into the system.

The station is equipped with a calling switch which can either activate a call bell, chime or other

equipment, or which can initiate a call to a preprogrammed station.

The HF-640S has an in-use lamp and is fitted with volume controls to adjust microphone sensitivity and speaker output level. The front panel of the HF-640S is made of stainless steel. The YC-150/YC150E flush-mounted back box and the YS-13 surface-mounted back box are available as optional accessories for easy installation.

#### **Specifications**

Microphone Impedance and Sensitivity:

1k ohm/-68dB omnidirectional electret condenser microphone

Speaker:  $8\Omega$ , 2-1/2 inch dynamic speaker

Dialing System: Amplitude modulated pulse

number code

Line Impedance: 600 ohms balanced

Audio Frequency

Range: 200Hz~7.5kHz

Calling Tone Signal

Output Level: 70dB/30cm

Wiring System: Non-polar 2-wire system

Current Consumption: 17mA (Max.)

Relay Contact Capacity

for Remote Control: DC 24V 1A

Ambient Temperature

Range: -10°C~+60°C (+14°F~+140°~F)

Weight: 0.27kg (0.6 lbs)

Optional Accessories: YC-150/YC-150E

Flush-mounted type Back Box

YS-13

Surface-mounted type Back Box

Associated Equipment: EX-600 2-wire Exchange

(Max. 32)

EX-610 2-wire Exchange

(Max. 64)

EX-620 2-wire Exchange


(Max. 128)


EX-630 2-wire Exchange


(Max. 256)

### **Architects and Engineers Specifications**

The intercom door station shall be TOA model HF-640S. The station shall provide a calling switch and an in-use lamp. Volume controls for adjustment of the microphone sensitivity and speaker output level shall be built in the station. The front panel of HF-640S shall be stainless steel. The flush-mounting back box shall be TOA model YC-150/YC150E and the surface-mounting back box shall be model YS-13.









Specifications are subject to change without notice.