

■ DESCRIPTION

The 22" Dynamic Display delivers crisp communication and instant messages to alert individuals. Integrated system to synchronized clocks for precise time, countdown timers and buzzers. The digital signage improves building communications and audio/visual cues to keep everyone informed. The screen keeps critical messages clear and timely during threats, with automatic and custom messages. Ability to integrate with other building systems like fire alarms, P.A., lockdown and even weather alerts.

■ SPECIFICATIONS

| | |
|--|---|
| Screen Lighting | LCD with LED backlight |
| Display Screen Resolution | 1920 x 1080 |
| Mounting Formats | Landscape (horizontal) or portrait (vertical) |
| Internal speakers | 2 each a 2W |
| USB 2.0 ports | 2 |
| External speaker output jack | 3.5mm |
| Wired LAN connectivity | 10/100M, RJ45 connector |
| Wireless LAN connectivity | 802.11b/g/n (2.4GHz) |
| USB provisioning | USB drive with AES encryption |
| Wired provisioning | LAN/DHCP Web portal on network connection |
| Time synchronization support | 2 static IP address time servers or pool SNTP domain name |
| Clock battery backup for power outages | CR1220 lithium |
| Maximum relative humidity | 85% |
| Operating temperature | 0°C - 40°C |
| Input voltage to power supply | 100-240VAC, 50/60Hz |
| Output voltage from power supply | 12VDC |
| Energy efficiency | Level VI |
| Power consumption | 9.5W (average), 14.5W (maximum) |
| Certifications | ROHS, CE/FCC, IC, PSU with NRCan |
| Dimensions (device only) | 20 13/16" L, 1-3/8" W, 12 9/16" H |
| Dimensions: display screen diagonal | 21.5" |
| Dimensions: master shipping carton, two displays | 38" L, 8-3/8" W, 18-1/2" H |
| Weight (device only) | 8 lbs |
| Weight: master shipping carton, two displays | 37 lbs |

■ FEATURES

| |
|---|
| Smart 22" class HD screen with built-in speakers |
| English and French Language Support |
| EverAlert platform supports a virtually unlimited number of displays |
| Display functions in either landscape or portrait orientation |
| Preloaded with operating system software |
| Communicates to the toalert management portal through wired Ethernet or Wi-Fi network |
| Resumes normal operation without intervention after a temporary power interruption |
| Operator adjustable or scheduled screen brightness |
| Scheduled sleep mode for energy conservation |